

createacct

Create Account

This is to create an eenos hosting account. You can also create a hosting account with reseller privileges.

Required Parameters

These parameters are mandatory, or else you will receive 400 error code.

Field	Description	Example
apiuser	API user name	eenos_api
apiauth	API user password	eenos123
domain	Client's main website name	myclientsite.com
user	A user name for eenos account	myclient
email	Contact email address of the client	contact@myclientsite.com
package	Hosting plan or package name	Bronze

Optional Parameters

Field	Description	Example
password	A password for Eenos login will be auto-generated if not given	changeme
language	The language code for the eenos control panel, default is 'en'	en
theme	If you have a custom theme name, the default theme is 'default'	default
mailserver	Use local or remote mail server, default 'local'	local
dkim	To enable dkim, values accepted 'off' or 'on'	off
spf	To enable spf, values accepted 'off' or 'on'	off

reseller	To make this account reseller, accepted values 'off' or 'on'	on
resellerself	Self-own accounts in case of reseller, values accepted 'off' or 'on'	on
use_registrar_ns	To use domain registrar NS records, accepted values 'off' or 'on'	on
ipv4	To enable dedicated IPv4, values accepted 'off' or 'on'. This will override the package feature	off
ipv6	To enable dedicated IPv6, values accepted 'off' or 'on'. This will override the package feature	off
shell	To enable jailshell access, values accepted 'off' or 'on'	off
reseller_bandwidth	Reseller combined bandwidth limit. Values accepted unlimited or number (MB)	unlimited
reseller_limt	Number of accounts reseller can create, values accepted unlimited or number	10
reseller_quota	Reseller combined disk quota, values accepted unlimited or number (MB)	20000
addondomains	Number of addon domains, values accepted unlimited or number	unlimited
parkeddomains	limit of Domain parking, values accepted unlimited or number	10
subdomains	Number of subdomains, values accepted unlimited or number	100
email_accounts	Number of email accounts, values accepted unlimited or number	150
ftp	Number of ftp accounts, values accepted unlimited or number	10
sql	Number of databases, values accepted unlimited or number	unlimited
bandwidth	Hosting account bandwidth limit, values accepted unlimited or number (MB)	50000
quota	Hosting account disk quota, values accepted unlimited or number (MB)	10000
mailquota	Hosting account default email quota, values accepted unlimited or number (MB)	512

Result Status Codes

Status Code	Description
200	Success
500	Server Error
403	Forbidden, demo server
400	Bad data request

Request URL

Post url = **/createacct/**

Full URL = <https://your-host-name:5555/api/createacct/>

Curl Code

```
#!/bin/bash
REQUEST_URL="/createacct/"
BASE_URL="https://your-host-name:5555/api/v1"
API_URL="$BASE_URL$REQUEST_URL"
/usr/bin/curl -X POST $API_URL \
  -d "apiuser=eenos_api" \
  -d "apiauth=eenos123" \
  -d "domain=myclientsite.com" \
  -d "user=myclient" \
  -d "email=contact@myclientsite.com" \
  -d "package=Browse"
```

Sample Output

```
{'data': {'addondomains': 'unlimited',
  'bandwidth': 'unlimited',
  'contactemail': 'contact@myclientsite.com',
  'dedicatedip': {'ipv4': 'xxx.xx.xx.xxx',
    'ipv6': '2a01:0xxx:0xxx:2xxx:0000:0000:0000:xxxx',
    'status': 'off',
    'status6': 'off'},
  'dkim': 'off',
  'domain': 'myclientsite.com',
```

```
'email': 'unlimited',
'feature': 'Default',
'ftp': 'unlimited',
'homedir': '/home/myclient',
'language': 'en',
'maillist': 'unlimited',
'mailquota': 'unlimited',
'mailserver': 'local',
'nameservers': ['ns1.eenos.com', 'ns2.eenos.com'],
'owner': 'root',
'package': 'Browse',
'parkeddomains': 'unlimited',
'quota': 'unlimited',
'reseller': {'selfown': 'off', 'status': 'off'},
'setuptime': '2022-12-12 07:47',
'shell': {'shell': '/sbin/nologin', 'status': 'off'},
'spf': 'off',
'sql': 'unlimited',
'subdomains': 'unlimited',
'theme': 'default',
'user': 'myclient'},
'info': 'Hosting account created successfully',
'status': 200}
```

Python Code

```
#!/usr/bin/python3
import requests
from pprint import pprint
# The API request url
request_url='/createacct/'
# The server api base url
base_url='https://your-host-name:5555/api'
# Default base url
# base_url='https://your-host-name:5555/api'
# Version specific base url
# base_url='https://your-host-name:5555/api/v1'
# The api url
api_ulr=base_url+request_url
```

```
# The data in dictionary format
data={
    'apiuser': 'eenos_api',
    'apiauth': 'eenos123',
    'domain': 'myclientsite.com',
    'user': 'myclient',
    'email': 'contact@myclientsite.com',
    'package': 'Browse'
}
try:
    result=requests.post(api_ulr, data = data)
    pprint(result.json())
except Exception as e:
    pprint(str(e))
pass
```

PHP Code

```
<?php
// The API request url
$request_url='/createacct/';

// Your server API base url
$base_url='https://your-host-name:5555/api';
// Default base url
// $base_url='https://your-host-name:5555/api';
// Version specific base url
// $base_url='https://your-host-name:5555/api/v1';
// The FULL API URL
$api_url=$base_url.$request_url;
//The data you want to send via POST
$fields= [
    'apiuser' => 'eenos_api',
    'apiauth' => 'eenos123',
    'domain' => 'myclientsite.com',
    'user' => 'myclient',
    'email' => 'contact@myclientsite.com',
    'package' => 'Brownse'
```

```
];  
//url-ify the data for the POST  
$fields_string = http_build_query($fields);  
//open connection  
$ch = curl_init();  
//set the url, number of POST vars, POST data  
curl_setopt($ch,CURLOPT_URL, $api_url);  
curl_setopt($ch,CURLOPT_POST, true);  
curl_setopt($ch,CURLOPT_POSTFIELDS, $fields_string);  
//So that curl_exec returns the contents of the cURL; rather than echoing it  
curl_setopt($ch,CURLOPT_RETURNTRANSFER, true);  
//execute post  
$result = curl_exec($ch);  
//Print the json result  
echo json_encode(json_decode($result), JSON_PRETTY_PRINT);  
?>
```

Revision #9

Created 12 December 2022 18:37:11 by Eenos Official Editor

Updated 11 December 2023 08:55:25 by Jessi