

suspendacct

Suspend Eenos Account

To suspend an eenos hosting account via API.

Required Parameters

Field	Description	Example
apiuser	API user name	eenos_api
apiauth	API user password	eenos123
user	eenos account user name	myclient

Optional Parameters

Field	Description	Example
reason	Reason for suspension	non-payment

Status Codes

Code	Description
200	OK, Success
500	Server Error
403	Forbidden
400	Bad request

Request URL

Post url = **/suspendacct/**

Default Full URL = <https://your-host-name:5555/api/suspendacct/>

Version Full URL = <https://your-host-name:5555/api/v1/suspendacct/>

Sample Curl Code

```

#!/bin/bash

REQUEST_URL="/suspendacct/"

BASE_URL="https://your-host-name:5555/api/v1"

# Default base url

# BASE_URL="https://your-host-name:5555/api"

# Version specific base url

# BASE_URL="https://your-host-name:5555/api/v1"

API_URL="$BASE_URL$REQUEST_URL"

/usr/bin/curl -X POST $API_URL \
-d "apiuser=eenos_api" \
-d "apiauth=eenos123" \
-d "user=myclient" \
-d "reason='no payment'"

```

Sample Output

```
{
  "data" : "User account suspended myclient",
  "info" : "Hosting account suspended successfully",
  "status" : 200
}
```

Python Code

```

#!/usr/bin/python3

import requests
from pprint import pprint

# The API request url
request_url='/suspendacct/'

# The server api base url
base_url='https://your-host-name:5555/api'

# Default base url

# base_url='https://your-host-name:5555/api'

# Version specific base url

# base_url='https://your-host-name:5555/api/v1'

# The api url

api_url=base_url+request_url

# The data in dictionary format

data={
```

```

'apiuser': 'eenos_api',
'apiauth':'eenos123',
'user':'myclient',
'reason':'non payment'

}

try:
    result=requests.post(api_ulr, data = data)
    pprint(result.json())

except Exception as e:
    pprint(str(e))
    pass

```

PHP Code

```

<?php
// The API request url
$request_url='/suspendacct/';

// Your server API base url
$base_url='https://your-host-name:5555/api';

// Default base url
// $base_url='https://your-host-name:5555/api';

// Version specific base url
// $base_url='https://your-host-name:5555/api/v1';

// The FULL API URL
$api_url=$base_url.$request_url;

//The data you want to send via POST
$fields= [
    'apiuser' => 'eenos_api',
    'apiauth' => 'eenos123',
    'user'     => 'myclient',
    'reason'   => 'non payment'
];

//url-ify the data for the POST
$fields_string = http_build_query($fields);

//open connection
$ch = curl_init();

//set the url, number of POST vars, POST data
curl_setopt($ch,CURLOPT_URL, $api_url);

```

```
curl_setopt($ch,CURLOPT_POST, true);
curl_setopt($ch,CURLOPT_POSTFIELDS, $fields_string);
//So that curl_exec returns the contents of the cURL; rather than echoing it
curl_setopt($ch,CURLOPT_RETURNTRANSFER, true);
//execute post
$result = curl_exec($ch);
//Print the json result
echo json_encode(json_decode($result), JSON_PRETTY_PRINT);
?>
```

Revision #3

Created 13 December 2022 12:06:26 by Eenos Official Editor

Updated 11 December 2023 08:59:18 by Jessi