

suspendreseller

Suspend Eenos Reseller Account

To suspend eenos reseller hosting account via API.

Required Parameters

Field	Description	Example
apiuser	API user name	eenos_api
apiauth	API user password	eenos123
user	eenos reseller account user name	myclient

Optional Parameters

Field	Description	Example
reason	Reason for suspension	non-payment

Status Codes

Code	Description
200	OK, Success
500	Server Error
403	Forbidden
400	Bad request

Request URL

Post url = **/suspendreseller/**

Default Full URL = <https://your-host-name:5555/api/suspendreseller/>

Version Full URL = <https://your-host-name:5555/api/v1/suspendreseller/>

Sample Curl Code

```
#!/bin/bash
REQUEST_URL="/suspendreseller/"
BASE_URL="https://your-host-name:5555/api/v1"
# Default base url
# BASE_URL="https://your-host-name:5555/api"
# Version specific base url
# BASE_URL="https://your-host-name:5555/api/v1"
API_URL="$BASE_URL$REQUEST_URL"
/usr/bin/curl -X POST $API_URL \
  -d "apiuser=eenos_api" \
  -d "apiauth=eenos123" \
  -d "user=myclient" \
  -d "reason='no payment'"
```

Sample Output

```
{
  "data" : "Reseller account suspended myclient",
  "info" : "Hosting reseller account suspended successfully",
  "status" : 200
}
```

Python Code

```
#!/usr/bin/python3
import requests
from pprint import pprint
# The API request url
request_url='/suspendreseller/'
# The server api base url
base_url='https://your-host-name:5555/api'
# Default base url
# base_url='https://your-host-name:5555/api'
# Version specific base url
# base_url='https://your-host-name:5555/api/v1'
# The api url
api_url=base_url+request_url
# The data in dictionary format
data={
```

```

'apiuser': 'eenos_api',
'apiauth': 'eenos123',
'user': 'myclient',
'reason': 'non payment'
}
try:
    result=requests.post(api_ulr, data = data)
    pprint(result.json())
except Exception as e:
    pprint(str(e))
    pass

```

PHP Code

```

<?php
// The API request url
$request_url='/suspendreseller/';
// Your server API base url
$base_url='https://your-host-name:5555/api';
// Default base url
// $base_url='https://your-host-name:5555/api';
// Version specific base url
// $base_url='https://your-host-name:5555/api/v1';
// The FULL API URL
$api_url=$base_url.$request_url;
//The data you want to send via POST
$fields= [
    'apiuser' => 'eenos_api',
    'apiauth' => 'eenos123',
    'user'    => 'myclient',
    'reason'  => 'non payment'
];
//url-ify the data for the POST
$fields_string = http_build_query($fields);
//open connection
$ch = curl_init();
//set the url, number of POST vars, POST data
curl_setopt($ch,CURLOPT_URL, $api_url);

```

```
curl_setopt($ch,CURLOPT_POST, true);
curl_setopt($ch,CURLOPT_POSTFIELDS, $fields_string);
//So that curl_exec returns the contents of the cURL; rather than echoing it
curl_setopt($ch,CURLOPT_RETURNTRANSFER, true);
//execute post
$result = curl_exec($ch);
//Print the json result
echo json_encode(json_decode($result), JSON_PRETTY_PRINT);
?>
```

Revision #4

Created 13 December 2022 12:37:51 by Eenos Official Editor

Updated 11 December 2023 09:05:27 by Jessi